

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)


PCT

(10) International Publication Number
WO 2005/063563 A1

- (51) International Patent Classification⁷: **B63H 3/00**, B64C 11/34 (74) Agents: **PELLEGRI, Alberto** et al.; c/o Società Italiana Brevetti S.p.A., Piazza Repubblica, 5, I-21100 Varese (IT).
- (21) International Application Number: PCT/IT2003/000878 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 30 December 2003 (30.12.2003)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (71) Applicant (*for all designated States except US*): **MARINE PROPELLER S.R.L.** [IT/IT]; Construzioni Eliche a Passo Variabile, Via C. Battisti, 35, I-21058 Solbiate Olona (IT).
- (72) Inventors; and (75) Inventors/Applicants (*for US only*): **BERGHELLA, Fabio** [IT/IT]; Via Cesare Battisti, 35, I-21058 Sobiate Olona (IT). **MASETTI, Franco** [IT/IT]; Via Piemonte, 12, I-20025 Legnano (IT).
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published: — with international search report

[Continued on next page]

(54) Title: SHOCK ABSORBER FOR ADJUSTABLE PITCH PROPELLER WITH FEATHERING BLADES, PARTICULARLY FOR SAILERS



(57) Abstract: According to an embodiment of this invention, a plurality of stops are implemented between metal surfaces that may be reached only in the event of shocks of great violence and in any case following a certain elastic deformation of the shock absorbing resilient inserts of elastomer, which in any case remains partial compared to full compressing of the elastomer beyond its super elastic limit. At the bottom of each circular cavity (15) housing a respective annular insert (16) of elastomer of the flange (14) of a first cylindrical sleeve (13) directly keyed on the drive shaft of the propeller a hole coaxial and of greater diameter than the diameter of the central hole of the annular insert of elastomer and of the relative engaging pin (19) is formed and the pins projecting from the face of the terminal flange of a second circular sleeve extend through the coaxially formed holes at the bottom of the respective circular cavities of the flange of the first sleeve.

WO 2005/063563 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.